



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H04B 7/26, H04Q 7/00, 7/04	A1	(11) International Publication Number: WO 93/12587 (43) International Publication Date: 24 June 1993 (24.06.93)
---	----	--

(21) International Application Number: PCT/FI92/00328

(22) International Filing Date: 2 December 1992 (02.12.92)

(30) Priority data:
915886 13 December 1991 (13.12.91) FI

(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Mäkkylän puistotie 1, SF-02600 Espoo (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only) : SALMELA, Mikko [FI/FI]; Nissnikuntie 1 D 14, SF-02430 Masala (FI).


(74) Agent: OY KOLSTER AB; Stora Robertsgatan 23, P.O. Box 148, SF-00121 Helsinki (FI).

(81) Designated States: AU, GB, JP, NO, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: CELLULAR RADIO SYSTEM



(57) Abstract

The invention relates to a cellular radio system comprising a plurality of base stations (BTS1-BTS4). Each base station comprises at least one radio transmitter (21, 22) and receiver (33, 34), an antenna means (ANT1) with a predetermined radio coverage area (CS1-CS2), and one or more allocated radio channels for establishing a radio connection with the mobile radio stations (MS) within the predetermined radio coverage area (CS1-CS4). The system comprises at least one base station (BTS5) including an antenna means that can be directed automatically or by remote control, depending on the time of the day or variation in regional traffic load.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	CN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TC	Togo
DE	Germany	MD	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Cellular radio system

Field of the invention

5 The invention relates to a cellular radio
system comprising a plurality of mobile radio stations
roaming in the system, a plurality of base stations,
each base station comprising at least one radio trans-
mitter and radio receiver, an antenna means with a
predetermined radio coverage area, and one or more allo-
10 cated radio channels for establishing a radio connection
with the mobile radio stations within the predetermined
radio coverage area, at least the base stations with
adjacent radio coverage areas having different allocated
radio channels.

15

Background of the invention

In cellular mobile radio networks the geo-
graphical area covered by the network is divided into
radio cells, each of which has at least one base sta-
20 tion. A certain number of frequencies (radio channels)
are allocated to each base station, and said channels
may in turn be shared by a plurality of TDMA (Time Divi-
sion Multiple Access) traffic channels. The size and
distribution of cells and the number of radio channels
25 available to them are typically determined by the
traffic capacity demand in said area. However, a
cellular mobile radio network may include cells or
larger areas where the traffic capacity demand may rise
temporarily, e.g. at particular times of the day, to a
30 very high level. If the number of radio channels in a
cell is set on the basis of said instantaneous maximum
capacity demand, the number of radio channels increases,
and consequently the amount and cost of radio equipment
in a base station also becomes higher. Further, this
35 kind of solution does not result in effective

utilization of radio frequencies in a network. On the other hand, if the number of radio channels and the equipment of the base station are not set on the basis of maximum traffic, the number of failed call attempts becomes very high in said area at peak hours.

Summary of the invention

The object of the invention is to overcome this problem.

This is achieved by a cellular radio system according to the invention, the system comprising at least one base station including an antenna means (ANT1, 44) that can be directed automatically or by remote control, depending on the time of the day or variation in regional traffic load.

The basic idea of the invention is that at least one base station may, by mechanically re-directing its antenna according to traffic demand, direct part or all of its capacity (radio and / or traffic channels) to the area of the radio cell where the traffic capacity demand has temporarily increased. An advantage of the invention is that the number of channels in a single radio cell need not be set on the basis of an instantaneous maximum capacity demand in said radio cell but it can be set on the basis of an average maximum capacity demand in a plurality of adjacent radio cells. If necessary, the traffic capacity of a single cell may be increased by directing part of the capacity of the neighboring cells thereto, whereby the capacity of the network may be effectively controlled regionally and a higher utilization of the equipment and frequency / traffic channels of the base stations may be accomplished. Also, more effective utilization of radio channels in the entire network is achieved with the invention.

This kind of base station with a directable antenna may also be a so called extra base station which does not actually have a cell of its own and which is located at the peripheral area of a plurality of cells to selectively increase traffic capacity.

Advantageously, a base station comprises a drive means for re-directing the antenna by turning it mechanically. This may be performed automatically or manually, remote controlled by an operator, from the control center of the system.

Brief description of the drawings

In the following the invention is described in greater detail by means of illustrating embodiments with reference to the attached drawing wherein

Fig. 1 shows a schematic view of a cellular mobile radio network in which the process of the present invention may be applied, and

Fig. 2 shows a block diagram of a transmitter section and a receiver section of a base station according to the invention.

A detailed description of the invention

The invention may be applied to regional control of traffic capacity of a mobile radio network in any digital mobile telephone or mobile radio system, such as the European mobile telephone system GSM (Groupe Special Mobile), and in an analogue mobile telephone or radio system, such as the Nordic Mobile Telephone system NMT. With regard to the basic idea of the invention the analogue and digital systems are identical although in a typical analogue mobile radio system one frequency, i.e. radio channel, provides one traffic channel, whereas in a typical digital mobile radio system the traffic capacity is higher since several, typically 8,

traffic channels are time division multiplexed to each radio channel on a TDMA principle, i.e. on one radio channel may be up to 8 simultaneous connections between a base station and mobile radios. The basic configuration and operation of the GSM and NMT mobile phone systems are well known to those skilled in the art and defined fairly accurately by the specifications of each system.

A mobile radio network may comprise one or more MSC areas, i.e. areas where services are provided by one mobile switching center MSC (mobile exchange). The MSC area may in turn consist of one or more location areas, which are areas covered by a plurality of radio cells. A cell is the smallest geographical area of the system, comprising one or more fixed radio transceivers or base transceiver stations BTS and utilizing predetermined radio channels.

Fig. 1 shows an embodiment of an MSC area or a location area of a cellular mobile radio network where the present invention may be applied. The geographic area covered by the cellular mobile radio network is divided in an essentially continuous manner into smaller radio areas, i.e. into radio cells CS1, CS2, CS3 and CS4, such that adjacent radio areas limit one another or overlap in their peripheral areas. Accordingly, in each radio cell CS1 to CS4 is located at least one fixed radio station or base station BTS1 to BTS4 capable of establishing a connection on the radio channels allocated to it, i.e. pairs of transmitting and receiving frequencies (duplex interval e.g. 45 Mhz), with the mobile radios MS currently located or roaming in its radio cells CS1 to CS4. It is typical that the radio channels allocated are different at least in adjacent radio cells. Each base station BTS has also signalling and traffic channel links with a mobile exchange MSC,

which controls the operation of one or more base stations within its MSC area. For the sake of simplicity it is assumed in the embodiment of Fig. 1 that all base stations BTS1 to BTS4 have a common mobile exchange MSC.

5 Each base station BTS1 to BTS4 of the cellular mobile radio network typically comprises at least one radio transmitter and one receiver; in the embodiment of Fig. 2, there are two radio transmitters 21 and 22 and two radio receivers 33 and 34 connected to an
10 antenna unit ANT1. The size and shape of the radio coverage (radiation pattern) of the antenna unit ANT1 determine the size and shape of the radio cell of the base station. The antenna unit ANT1 may comprise separate antennae for transmitting and for receiving.

15 In the transmitter section of the base station radio transmitters 21 and 22 are connected directly to a combiner 24 combining the radio frequency transmission signals of the radio transmitters 21 and 22 and feeding the combined signal to the antenna unit ANT1.

20 In the receiver section of the base station the antenna unit ANT1 is connected to radio receivers 33 and 34 via a distribution amplifier unit 32.

 Normally the base station BTS has a fixed coverage area determined by the radiation patterns of
25 one omnidirectional antenna or, alternatively, of one or more directional antennae. All the radio channels of the base station are within the coverage area of the main antenna unit ANT1, i.e. available to the mobile radios in the radio cell of the base station.

30 However, situations occur where e.g. the traffic in the radio cell CS4 may temporarily exceed the capacity of the base station BTS4 of the cell. For example, the area covered by the cell CS4 may include the end of a motorway which is the main entry to the
35 city and where traffic jams between 7.00 and 8.30 am.

Correspondingly, the area covered by another radio cell CS1 may include e.g. an industrial and office area where the most telephone traffic occurs between 8.30 and 16.00. The cell CS2 may cover an area including a sports stadium or a fair area and the capacity demand for telephone traffic is high when events are organized therein.

If the number of radio channels in the base stations BTS is determined in view of the peak hours, the utilization of the radio channels is low at the system level.

The system of the invention comprises at least one base station with an antenna / antennae directable, depending on the regional variation in traffic load, to the near-by areas currently requiring the most traffic capacity. In the embodiment of Fig. 1 the cells CS1, CS2 and CS4 have in their vicinity a base station BTS5 which has an antenna with a radiation pattern that can, if necessary, be directed to the directions 1, 2 and 3 to compensate and eliminate load peaks of telephone traffic in the cells at different times.

Fig. 3 illustrates a few possible ways to control the directing of the radiation pattern of the antenna in the base station BTS5. The base station BTS5 is identical to the base stations BTS1 to BTS4 in its basic structure but, in addition, it includes a mechanical drive means 43 connected to a frame 45 (mast) for re-directing the directional antenna unit 44 (usually includes different antennae for transmitting and receiving) by turning the antenna unit. The drive means is, for example, a step-by-step controllable electric motor 43, which may turn the antenna unit 41 at least in a horizontal plane, advantageously also in a vertical plane. Vertical directability is advantageous e.g. when the antenna unit is located at a high location since the antenna unit can then be directed to a near-by area at

a lower level by inclining the antenna towards the area in a vertical plane. Also the length of the antenna lobe (radiation pattern) may be affected by turning the antenna in a vertical plane.

5 The antenna turning means 43 may be controlled in many ways, some of which are illustrated in Fig. 3. The directability of the antenna 44 in response to different times of the day and the corresponding control operations of the turning means 43 may be automatic and
10 permanently programmed to a particular timer unit 42. Thereby the antenna of the base station BTS5 may be re-directed automatically depending on the time of the day and / or the day of the week, e.g. such that from 7.00 to 8.30 am the antenna of the base station BTS5 assumes
15 the direction 1 (motorway), from 8.30 to 16.00, the direction 2 (office and industrial area), and when events are arranged at the sports stadium, the direction 3.

20 Alternatively, the turning means 43 of the antenna 44 may be controlled by remote control from the control center 41 of the radio system either manually or by preprogramming depending on the time and the loading of the network.

25 Further, the radio system may comprise a separate capacity control unit OMCRN, which, depending on the time and / or the loading of the system, automatically directs channel capacity to the loaded areas by controlling e.g. the antenna turning unit 43 of the base station BTS5. The system may comprise one OMCRN
30 unit for the entire system or several OMCRN units, each of which controls part of the system. An OMCRN unit also makes it possible to take into account the effect the directing of the antennae has on elsewhere in the radio network. An OMCRN unit or the corresponding operations
35 may also be integrated to a mobile exchange MSC. For

example, a mobile exchange MSC (or another element in the network) may, on detecting overloading of a base station BTS1, generate an alarm to a capacity control unit OMCRN, whereby the OMCRN instructs the turning
5 means 43 of the base station to turn the antenna 44 to the direction 2.

The Figs. and the account thereof are intended only to illustrate the present invention. In its details the radio system according to the invention may vary
10 within the scope of the attached claims.

Claims

1. A cellular radio system comprising a plurality of mobile radio stations roaming in the system, a plurality of base stations (BTS1-BTS4), each base station comprising at least one radio transmitter (21,22) and radio receiver (33,34), an antenna means (ANT1) with a predetermined radio coverage area (CS1-CS2), and one or more allocated radio channels for establishing a radio connection with the mobile radio stations (MS) within the predetermined radio coverage area (CS1-CS4), at least the base stations with adjacent radio coverage areas having different allocated radio channels, c h a r a c t e r i z e d in that the system comprises at least one base station (BTS5) including a directional antenna means (ANT1,44) having means (43) for redirecting the radiation pattern of the antenna means automatically or by remote control, depending on the time of the day or variation in regional traffic load.

2. A cellular radio system according to claim 1, c h a r a c t e r i z e d in that said at least one base station (BTS5) comprises drive means (43) for re-directing the antenna means (44) by turning it mechanically.

3. A cellular radio system according to claim 1 or 2, c h a r a c t e r i z e d in that the antenna means is automatically directable in response to the time of the day and / or the day of the week.

4. A cellular radio system according to claim 1 or 2, c h a r a c t e r i z e d in that the antenna means is directable automatically or manually to the near-by areas currently requiring the most traffic capacity.

5. A cellular radio system according to claim

10

1 or 2, characterized in that the system comprises means (OMCRN) for re-directing the antenna means (44) on the basis of an overload alarm generated by an element in the system.

5 6. A cellular radio system according to any one of the preceding claims, characterized in that the system is a digital cellular radio system and that each radio channel comprises a plurality of TDMA traffic channel time slots.

10 7. A cellular radio system according to any one of claims 1 to 5, characterized in that the system is an analogue cellular radio system.




FIG. 1




FIG. 2




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 92/00328

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: H04B 7/26, H04Q 7/00, H04Q 7/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: H04B, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CLAIMS, WPI, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO, A1, 9212601 (MOTOROLA INC.), 23 July 1992 (23.07.92), page 11, line 4 - line 32 --	1,4,6,7
P,Y	WO, A1, 9216061 (TELENOKIA OY), 17 Sept 1992 (17.09.92), page 2, line 28 - page 4, line 11; page 5, line 1 - line 20 --	1,6,7
Y	EP, A2, 416872 (MOTOROLA INC.), 13 March 1991 (13.03.91), column 4, line 31 - line 45 ---	1,6,7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 March 1993

Date of mailing of the international search report

16 -03- 1993

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Bo Gustavsson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 92/00328

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP, A1, 399206 (MOTOROLA INC.), 28 November 1990 (28.11.90), column 2, line 39 - line 48 -----	1

INTERNATIONAL SEARCH REPORT
Information on patent family members

29/01/93

International application No.

PCT/FI 92/00328

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO-A1-	9212601	23/07/92	CN-A-	1063790	19/08/92
WO-A1-	9216061	17/09/92	AU-A-	1359092	06/10/92
EP-A2-	416872	13/03/91	NONE		
EP-A1-	399206	28/11/90	NONE		